






PARTS

- A** top horizontal rail - (2) 2 x 4 x 53 ³/₄" (see drawing)
- B** bottom horizontal rail - (2) 2 x 4 x 54" (see drawing)
- C** vertical supports - (4) 2 x 4 x 54"
- D** side rails - (2) 2 x 4 x 12"
- E** seat slats - (6) ⁵/₈" x 5" x 15"
- F** side strips - (8) ⁵/₈" x 2 ¹/₄" x 12"
- G** lower seat cleat - (1) 2 x 4 x 31" (see drawing)
- H** upper seat cleat - (1) 2 x 4 x 37" (see drawing)
- I** back seat slats - (6) ⁵/₈" x 5" x 16" (see drawing)
- J** top strips & side seat strips - (16) ⁵/₈" x 2 ¹/₄" x 17"

HORIZONTAL RAILS & VERTICAL SUPPORTS





Fasten the upper and lower horizontal rails to the vertical supports with glue and 2 1/2" screws.




SIDE RAILS

Fasten the side rails to the vertical supports with glue and 2 1/2" screws.





TEMPORARY SUPPORT & SEAT SLATS

Fasten the seat slats to the front and back rails with glue and 1 5/8" screws.




SIDE STRIPS



Fasten the side strips to the front and back vertical supports with glue and 1 5/8" screws.



LOWER SEAT CLEAT




UPPER SEAT CLEAT




BACK SEAT SLATS

Lay the slats on a flat surface and draw an arc across the tops of the slats.



Cut the arc in the slat pieces.



TOP STRIPS & SIDE SEAT STRIPS

